



Add:1209 Room,2 Build, No. 1588 of Huhang Road , Shanghai City, China.

Protect SVP

Prevent spandex fabric from lossing elasticity and foaming in washing, anti-sliding and anti-cracking

Description:

Avoid lossing elasticity during washing on denim elastic fabric, foaming and large size, to prevent yarn slipping and cracking.

Performance:

- >Used for bulletproof and yarn with spandex elastic denim
- >Prevent spandex filament from coating yarn and sliding during washing
- >With excellent adhesion, penetration into the fiber interior plays a fixed protection role
- >It can also be used as yarn or fabric anti-slip and crack, anti-pilling resistance
- >No free formaldehyde, APEO and other prohibited substances, to meet the environmental requirements of the EU

Physical and chemical characteristics

Anti-pilling resistance

Appearance	Milky white transparent to translucent liquid
pH	3.0-5.0
Ionicity	Anion
Solubility	Miscible with cold water in any proportion
Composition	Super NM contains silicon microemulsion

Reference process

Reference dosage: 0.5-1.5g/L

1、Spandex anti-loss process:

Before into the water, match Fashion protect SVP according to the required concentration, and then soak the clothing in the working liquid or run for 10-15 minutes for dehydration and drying.

2、As an anti-slip removal or anti-splitting process:

Add Fashion protect SVP in the after-treatment or together with softener, dehydration and drying.

3、As a cutting and anti-wrinkle process:

Before the pants or clothing in the cut treatment, first soak with Fashion protect SVP, and then dehydration and drying can do the cutting process, has a stable size, the pants flat does not play the role of wrinkle.

4、Application for desizing and enzyme washing process:

Add Fashion protect SVP to the washing equipment firstly, run for 1-3 minutes, then add other washing aids, and wash the corresponding time according to the washing process requirements.

When used with other chemicals in same bath, pay attention to the ionicity of product and avoid the cation product in same bath.

Package and storage

120kg/plastic drum.

Store it in a cool and dry place where is under 25 °C, avoid direct sunlight and the shelf life is for 6 months under sealing conditions.