

SILIT-2350

TECHNICAL DATA SHEET

SILIT-2350 is a kind of macro silicone emulsion, which is easy to be diluted. It is used for softener of textiles such as cotton and its blend fabrics. It has super slippery and some soft handfeeling.

Characteristics

- Some soft handfeeling
 - Super slippery handfeeling
 - Low yellowing and low color shading
-

Properties

| | |
|------------------|-----------------|
| Appearance | macro liquid |
| pH value, approx | 5-7 |
| Ionicity | slight cationic |
| Solubility | water |
| Solid content | 50% |

Applications

1 Exhaustion process:

| | |
|-----------------------------|-------------------------------|
| SILIT-2350 (50%emulsion) | 0.2~3%o.w.f. (After dilution) |
|-----------------------------|-------------------------------|

Usage :40°C~50°C×15~30min

2 Padding process:

| | |
|-----------------------------|--------------------------|
| SILIT-2350 (50%emulsion) | 2~30g/L (After dilution) |
|-----------------------------|--------------------------|

Usage :double-dip-double-nip

Package

SILIT-2350 is available in 200kg plastic drums.

Storage and shelf-life

When stored in its original packaging at a temperature of between -20°C and +50°C, **SILIT-2350** may be stored for up to 12 months from its date of manufacture (expiry date). Comply with the storage instructions and expiry date marked on the packaging. Past this date, **Shanghai Honneur Tech** no longer guarantees that the product meets the sales specifications.
